

TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, COVESTRO LLC MAKES NO EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY SPECIAL PURPOSE OR ANY IMPLIED WARRANTIES ARISING THROUGH TRADE, USAGE, COURSE OF DEALING OR COURSE OF PERFORMANCE, AS TO THE PRODUCT, IMPACT OF THE PRODUCT ON THE VALUE OF YOUR HOME OR ANY ENERGY OR COST RELATED SAVINGS AS A RESULT THEREOF. SOME STATES DO NOT ALLOW EXCLUSIONS OR LIMITATIONS OF AN IMPLIED WARRANTY, SO THE ABOVE EXCLUSIONS MAY NOT APPLY TO YOU. COVESTRO LLC SHALL NOT BE LIABLE FOR PUNITIVE, CONSEQUENTIAL OR INCIDENTAL DAMAGES ARISING OUT OF THE PRODUCT OR USE THEREOF. SOME STATES MAY NOT ALLOW THE EXCLUSION OF PUNITIVE, CONSEQUENTIAL AND INCIDENTAL DAMAGES, SO THE ABOVE EXCLUSION OR LIMITATION MAY NOT APPLY TO YOU.



The manner in which you use and the purpose to which you put and utilize our products, technical assistance and information (whether verbal, written or by way of product evaluations), including any suggested formulations and recommendations are beyond our control. Therefore, it is imperative that you test our products, technical assistance and information to determine to your own satisfaction whether our products, technical assistance and information are suitable for your intended uses and applications. This application specific analysis must at least include testing to determine suitability from a technical as well as health, safety, and environmental standpoint. Such testing has not necessarily been done by us. Unless we otherwise agree in writing, all products are sold strictly pursuant to the terms of our standard conditions of sale which are available upon request. All information and technical assistance is given without warranty or guarantee and is subject to change without notice. It is expressly understood and agreed that you assume and hereby expressly release us from all liability, in tort, contract or otherwise, incurred in connection with the use of our products, technical assistance, and information. Any statement or recommendation not contained herein is unauthorized and shall not bind us. Nothing herein shall be construed as a recommendation to use any product in conflict with any claim of any patent relative to any material or its use. No license is implied or in fact granted under the claims of any patent.

*Savings vary. Find out why in the seller's fact sheet on R-values. Higher R-values mean greater insulating power. Actual savings may vary depending on type of home, weather conditions, occupant lifestyle, energy prices and other factors. No specific guaranty or warranty of energy or costs savings is being given and all such guaranties or warranties are expressly disclaimed.

EcoBay™ CC for Commercial Builders

An integrated insulation solution for well sealed energy efficient building



2400 Spring Stuebner Rd.
Spring, TX 77389
1 800 221 3626
Tel 281 350 9000
Fax 281 288 6450

www.polyurethanes.covestro.com



EcoBay™ CC for Commercial Builders

EcoBay™ spray polyurethane foam insulation for commercial builders is code compliant for Type I-V construction



An integrated insulation solution for well sealed energy efficient building

EcoBay™ CC spray foam insulation provides a solution to energy efficiency, durability, and improved occupant comfort in commercial building projects. When properly installed, EcoBay™ CC spray foam insulation material offers low installation cost, design flexibility and creates a durable effective thermal envelope. EcoBay™ CC can be spray-applied to walls, ceiling, floors, foundations, piping, and unvented attics. EcoBay™ CC offers an aged R-value of 6.9 per inch and is an ideal thermal and moisture management system that seals the building envelope for optimal insulation value. These benefits have a positive impact on the environment by reducing the carbon footprint.

EcoBay™ CC closed cell spray foam insulation for commercial builders

EcoBay™ CC insulation should be installed by professional spray foam contractors. Closed-cell foam insulation is a cost effective method to adopt a sustainable building approach and reduce energy consumption.

Construction Benefits

Continuous insulation on the building exterior eliminates thermal bridging.

1. EcoBay™ CC between framing increases racking strength.
2. Performance Benefits: EcoBay™ CC, at 1 inch or greater thickness, constitutes a Class II vapor retarder.
3. EcoBay™ CC functions as an integral component of an air barrier system
4. EcoBay™ CC is self-sealing around building penetrations: masonry ties, plumbing, conduit
5. Meets new ASHRAE 90.1 standards for continuous insulation standard at lowest installed thickness
6. Self-adhering to vertical surfaces

Key product benefits

EcoBay™ CC offers the benefit of continuous insulation. Continuous insulation eliminates thermal breaks and provides an air tight seal of the building envelope. When EcoBay™ CC is used as continuous insulation on the exterior of the building shell, there is no need for an additional building wrap as a drainage plane.

- Offers a high insulation R-value for maximum energy efficiency
- Provides a seamless air barrier that minimizes air leakage and energy loss
- Restricts moisture transmission
- Minimizes the conditions necessary for mold growth
- Adds structural strength
- Provides a drainage plane when installed as continuous insulation
- Does not shrink or settle

How to Get Started

Contact a Regional Representative today to learn how to request EcoBay™ CC through your builder or for a list of recommended spray foam insulation contractors in your area.

EcoBay™ CC as continuous exterior insulation

Wall Construction	Cladding / Veneer	Approved Construction Type (1)	Test (2)
Steel Stud	stucco	I, II, III, IV, VA, VB	E119, NFPA 285
	limestone	I, II, III, IV, VA, VB	E119, NFPA 285
	brick	I, II, III, IV, VA, VB	E119, NFPA 285
	CMU	I, II, III, IV, VA, VB	E119, NFPA 285
CMU	stucco	I, II, III, IV, VA, VB	E119, NFPA 285
	limestone	I, II, III, IV, VA, VB	E119, NFPA 285
	brick	I, II, III, IV, VA, VB	E119, NFPA 285
	CMU	I, II, III, IV, VA, VB	E119, NFPA 285
Concrete	stucco	I, II, III, IV, VA, VB	E119, NFPA 285
	limestone	I, II, III, IV, VA, VB	E119, NFPA 285
	brick	I, II, III, IV, VA, VB	E119, NFPA 285
	CMU	I, II, III, IV, VA, VB	E119, NFPA 285

(1) **Construction Type** – Types I & II are those types of construction that are mostly noncombustible materials as listed in IBC table 601. Types III construction is the type of construction in which the exterior walls are of noncombustible materials and the interior building elements are of any material permitted by IBC code Section 2303.2. Types V are those types of construction in which the structural elements, exterior walls, and interior walls are of any materials permitted by the IBC code
 (2) **E119** – Through Wall Fire Test and **NFPA 285** Flame Spread Outside Wall

Standout from conventional contractors by offering a product that delivers energy savings on heating and cooling, allows for consistent indoor temperatures, adds structural stability, is designed for advanced moisture management, and contributes to indoor air quality.

EcoBay™ CC as cavity fill between Framing

Wall Construction	Cladding / Veneer	Approved Construction Type (1)	Test (2)
Steel Stud- 1 1/2" CC (minimum)	stucco (& EFIS if meets NFPA 285)	I, II, III, IV, VA, VB	E119, NFPA 285
	limestone	I, II, III, IV, VA, VB	E119, NFPA 285
	brick	I, II, III, IV, VA, VB	E119, NFPA 285
	CMU & Precast	I, II, III, IV, VA, VB	E119, NFPA 285
	Concrete metal panel*	I, II, III, IV, VA, VB	E119, NFPA 285
	Hardy Plank	I, II, III, IV, VA, VB	E119, NFPA 285

* Noncombustible core

Effective R-Value for Continuous Insulation Uninterrupted by Framing Compared to Installation Between 3.5 inch Metal Studs (from ASRAE 90.1-2007, Table A3.1D)

