



Covestro LLC
2400 Spring Stuebner Road
Spring, TX 77389

Telephone
800-221-3626
Fax
281-288-6450

September 1, 2015

Recommended Bayseal™ CC X In-Service Temperatures

To Whom It May Concern,

The minimum recommended in-service temperature for Bayseal™ CC X and Bayseal™ CC XP is -40 °F (-40 °C). The maximum recommended in-service temperature for Bayseal™ CC X and Bayseal™ CC XP is 180 °F (82 °C).

Please contact me directly if you need further information.

Richard R. Romero
Spray Polyurethane Foam Technical Manager

Disclaimer: The manner in which you use and the purpose to which you put and utilize our products, technical assistance and information (whether verbal, written or by way of production evaluations), including any suggested formulations and recommendations, are beyond our control. Therefore, it is imperative that you test our products, technical assistance and information to determine to your own satisfaction whether our products, technical assistance and information are suitable for your intended uses and applications. This application-specific analysis must at least include testing to determine suitability from a technical as well as health, safety, and environmental standpoint. Such testing has not necessarily been done by us. Unless we otherwise agree in writing, all products are sold strictly pursuant to the terms of our standard conditions of sale which are available upon request. All information and technical assistance is given without warranty or guarantee and is subject to change without notice. It is expressly understood and agreed that you assume and hereby expressly release us from all liability, in tort, contract or otherwise, incurred in