



Tyvek.

DUPONT™ TYVEK® FLEXWRAP™ NF



DuPont™ FlexWrap™ NF addresses the issues of flashing vulnerable bottom corners of the sill where water damage is most likely to occur.

An integral component of DuPont Weatherization Systems, DuPont™ FlexWrap™ NF is a conformable, self-adhesive flashing solution for sills and non-straight portions of windows, doors and other wall penetrations.

DuPont™ FlexWrap™ NF is a premium performance, extendable self-adhered flashing material that can be applied over a wide range of building substances, including non-nailable sheathing materials like PS foam board, fiberboard, concrete masonry unit (CMU) and other such materials. DuPont™ FlexWrap™ NF does not require the use of mechanical fasteners in the flexed corner areas when installed according to the flashing installation guidelines issued by DuPont.

DuPont™ FlexWrap™ NF also flashes round-top or custom-shaped windows in a seamless manner, eliminating the need to cut and place individual pieces of conventional flashing on an arched opening.

BENEFITS

Superior protection from water damage

- Helps seal the building envelope when used with DuPont Weatherization Systems products
- Meets the AAMA 711-13 material standard at the highest classification levels: Class A (no primer) and Level 3 Thermal Exposure (80°C / 176°F for 7 days)
- Can be installed at external temperatures as low as -4°C (25°F) as long as the surface is clean and free from frost and ice

Easy installation

- Packaged in ready-to-use 6", 9" x 75 ft rolls
- Helps to facilitate the creation of airtight and water tight seals around windows, door sills, chimney breasts, pipe penetrations, and any custom shapes.

Superior durability

- Extendable flashing constructed with a durable, micro-creped DuPont™ Tyvek® top-sheet, a premium butyl adhesive layer, and a specially designed release liner
- Designed to withstand up to 270 days of UV exposure

Excellent adhesion performance

- Butyl adhesive performs through extreme temperatures
- Adheres to most common building materials



Easy to install material that can be applied over a wide range of building materials.



DUPONT™ FLEXWRAP™ NF BUILDING SCIENCE BULLETIN

DUPONT™ TYVEK® SPECIALIST NETWORK

A national group of highly trained field representatives is available to assist you with your installations. From the latest updates on building codes, to keeping up with current trends and challenges, your local DuPont™ Tyvek® Specialist can provide on-site consulting and training to help make sure the job gets done right.



COMPLETE SYSTEM OF PRODUCTS

For optimal protection on all your building projects, use DuPont™ FlexWrap™ NF with the complete line of DuPont Weatherization Systems products, including:

DuPont™ Tyvek® HomeWrap®

DuPont™ Tyvek® StuccoWrap®

DuPont™ Tyvek® DrainWrap™

DuPont™ Tyvek® ThermaWrap™ R5.0

DuPont™ Tyvek® ThermaWrap™ LE

DuPont™ RoofLiner,

DuPont™ StraightFlash™

DuPont™ StraightFlash™ VF

DuPont™ Tyvek® Tape,

DuPont™ Residential Sealant

DuPont™ Tyvek® Wrap Caps

LIMITED WARRANTY

DuPont™ FlexWrap™ NF is backed by a limited warranty. To learn more about the system that's right for you and to contact a DuPont™ Tyvek® Specialist in your area, visit www.weatherization.tyvek.com or call 1-800-44-Tyvek.

DUPONT™ TYVEK® CERTIFIED INSTALLERS

The DuPont™ Tyvek® Certified Installer Program is one more way to put the building science expertise of DuPont right at your fingertips. Your DuPont™ Tyvek® Certified installer provides trained installation services to help seal the building envelope.



For more information about DuPont™ Tyvek® FlexWrap™ NF, please call 1-800-44-Tyvek or visit us at www.weatherization.tyvek.com