

Insulation Certificate

This form must be filled out and posted to comply with building code requirements. Meets IRC Sections N1101.3, N1101.41, and N1101.8 requirements.

The following spray polyurethane foam product(s) has/have been installed:

] Bayseal® OC Open-Cell Spray Foam Insulation

ſ

ſ

[] Bayseal® OCX Open-Cell Spray Foam Insulation

] Bayseal® CC X Closed-Cell Spray Foam Insulation

] Bayseal® CC XP Closed-Cell Spray Foam Insulation

Consult International Building Code, Chapter 26-Plastic and International Residential Code (IRC) R314 Foam Plastics for specific requirements. The spray polyurethane foam insulation system(s) has/have been installed in accordance with manufacturer's processing guidelines to provide a thermal resistance of:

Area Insulated	Aged R-Value		Thickness*	
Attic Area	R-	At	inches	
Sloped Ceilings	R-	At	inches	
Walls (Location):	R-	At	inches	
Walls (Location):	R-	At	inches	
Floors (over an unheated crawl space)	R-	At	inches	
Crawl Space Perimeter	R-	At	inches	
Basement Exterior Walls	R-	At	inches	
Other (Location):	R-	At	inches	

*Nominal thicknesses are representative of field, spray-applied foam material

INSULATION CERTIFICATE - DO NOT REMOVE -Please Post Near Electrical Panel

2400 Spring Stuebner Rd West Spring, TX 77389 1.800.221.3626 Tel 281.350.9000 Fax 281.288.6450 www.accellapolyurethane.com