

Five Reasons LP® TopNotch® 350 Truly is Top-Notch.

1

Moisture Resistance

Our RainChannel™ technology creates a system that allows water to drain through the notches along the tongue and groove as well as the panel ends during construction. LP sub-flooring products are made with thermal-set resins and waxes and include a moisture-resistant edge sealant.

2

Easy Installation

With a self-spacing tongue and groove system, LP® TopNotch® panels are specially engineered to fit together with ease, which reduces installation time. This self-spacing profile, along with a fully sanded surface, helps ensure that the floor is level from panel to panel.

5

Warranty

All of these features create a sub-flooring product that will last. LP TopNotch 350 is backed by a 100-Day No-Sand Warranty and a 50-Year Transferable Limited Warranty. See LPCorp.com for complete warranty details.

LP TopNotch® 350 SERIES
50 YEAR
TRANSFERABLE
LIMITED WARRANTY

3

Strength & Stability

The OSB manufacturing process creates strength and uniform density throughout the product. This helps to provide a stable, solid sub-flooring with lasting durability.

4

Consistency

Unlike plywood, LP TopNotch sub-flooring is consistently flat and won't split or delaminate, which can help builders save time by easing installation on the job site.

LP **TOPNOTCH® 350**
BUILDING PRODUCTS PREMIUM OSB SUB-FLOORING

LPCorp.com/TopNotch