

AmPEX - Insulated Radiant PEX Panel – Special Order

SPECIAL ORDER			
AMPEX2515F	AMPEX2520F	AMPEX3015F	AMPEX3020F
1.5 lbs./ft ³	2.2 lbs./ft ³	1.5 lbs./ft ³	2.2 lbs./ft ³
12°F.ft ² .h/Btu	13°F.ft ² .h/Btu	14°F.ft ² .h/Btu	15°F.ft ² .h/Btu
28.0 psi	45.5 psi	28.0 psi	45.5 psi
51.9 psi	68.6 psi	51.9 psi	68.6 psi
23.8 (ng/Pa.s.m ²) 0.42 Perms	17.5 (ng/Pa.s.m ²) 0.31 Perms	23.8 (ng/Pa.s.m ²) 0.42 Perms	17.5 (ng/Pa.s.m ²) 0.31 Perms
49.25" x 25.25"	49.25" x 25.25"	49.25" x 25.25"	49.25" x 25.25"
125.10 x 64.14	125.10 x 64.14	125.10 x 64.14	125.10 x 64.14
48" x 24"	48" x 24"	48" x 24"	48" x 24"
122 x 61	122 x 61	122 x 61	122 x 61
3 7/8"	3 7/8"	4 3/8"	4 3/8"
9.84	9.84	11.11	11.11
2.5"	2.5"	3.0"	3.0"
6.35	6.35	7.62	7.62
Type II	Type IX	Type II	Type IX
Type 2	Type 3	Type 2	Type 3
3/8", 1/2", 5/8", 3/4" 1"	3/8", 1/2", 5/8", 3/4" 1"	3/8", 1/2", 5/8", 3/4" 1"	3/8", 1/2", 5/8", 3/4" 1"
.95, 1.27, 1.58, 1.91, 2.54	.95, 1.27, 1.58, 1.91, 2.54	.95, 1.27, 1.58, 1.91, 2.54	.95, 1.27, 1.58, 1.91, 2.54
16	16	14	14
144	144	128	128
92	92	92	92
1472	1656	1288	1288

*NOTE: Actual units per truckload may vary depending on trailer configuration.