



# A PROFESSIONAL'S CHOICE PROPINK® WALL INSULATION SYSTEM

For more information on Owens Corning Insulation products, contact your Owens Corning dealer, visit our web site at [www.owenscorning.ca](http://www.owenscorning.ca) or call **1-800-GET-PINK®**.

THE PINK PANTHER™ & © 1964 - 2014 Metro-Goldwyn-Mayer Studios Inc. All Rights Reserved. The colour PINK is a registered trademark of Owens Corning. © 2014 Owens Corning. All Rights Reserved. 73% recycled content is based on the average recycled glass content in all Owens Corning fiberglass batts, rolls and unbonded loosefill insulation manufactured in Canada. Owens Corning PINK insulation is GREENGUARD Certified for indoor air quality, except bonded loosefill products.

\* The thermal resistance of an insulating system is the measure of its resistance to heat flow. The higher the R (rsi) value, the greater the insulating power. Ask your seller for the fact sheet on thermal resistances. To get the marked R-value, it is essential that insulation be installed properly.

\*\* This device has been designed for use with the Owens Corning™ PROPINK® Wall Insulation System exclusively and cannot be used with other fabrics or insulation systems.

† DOES NOT SUPPORT MOULD GROWTH. As manufactured, fibre glass insulation is resistant to mold growth. (ASTM C1338-96 Fungi Resistance of Insulation Materials and Facings.) However, mould growth can occur on building materials, including insulation, when it becomes contaminated with organic material and when water is present. To avoid mould growth on fibre glass insulation, remove any water that has accumulated and correct or repair the source of that water as soon as possible. Insulation that has become wet should be inspected for evidence of residual moisture and contamination, and any insulation that is contaminated should be promptly removed and replaced.

†† The surface burning characteristics of these products have been developed in accordance with CAN/ULC-S102. This standard should be used to measure and describe the properties of materials, products or assemblies in response to heat and flame under controlled laboratory conditions and should not be used to describe or appraise the fire hazard or fire risk of materials, products or assemblies under actual fire conditions. However, results of this test may be used as elements of a fire risk assessment which takes into account all of the factors which are pertinent to an assessment of the fire hazard of a particular end use.



**OWENS CORNING CANADA LP**  
3450 MCNICOLL AVENUE  
SCARBOROUGH, ONTARIO  
M1V 1Z5

**1-800-GET-PINK®**  
[www.owenscorning.ca](http://www.owenscorning.ca)

Pub No. 200185C  
Printed in Canada, July 2015





# PROPINK® WALL INSULATION SYSTEM

## ONE OF THE BEST JUST BLEW IN - FAST. EFFECTIVE. MEASURABLE.

When you want an insulation job done fast and with the utmost quality, there's no better choice than the PROPINK® Wall Insulation System with the Inspect-R® Density Gauge.

Perfect for both new and retrofit projects, the PROPINK® Wall Insulation System blows smoothly and quickly into any wall or ceiling cavity, providing complete compression and gap-free coverage.

### MEASURE R-VALUES WITH INSPECT-R® DENSITY GAUGE

An alternative to roll or batt insulation, the PROPINK® Wall Insulation System can achieve thermal resistances\* of:

- Up to R-14 (rsi 2.47) for 2x4 construction
- Up to R-24 (rsi 4.23) for 2x6 construction

PROPINK® Wall Insulation System is a blown-in wall system that provides a non-invasive gauge to accurately measure the density of loosefill insulation in the walls to assure proper thermal resistance.

Our exclusive Inspect-R® Density Gauge\*\* is incredibly easy to use. Just place this handy tool against a newly insulated surface for an accurate, non-destructive reading in seconds.



Inspect-R® Density Gauge accurately reads R-values in seconds.



Fabric staples to studs quickly.



System provides complete compression and gap-free coverage.

## A COMPLETE SOLUTION

The PROPINK® Wall Insulation System includes PROPINK® FIBERGLAS® Blown Insulation, PROPINK® Complete™ Nonwoven Fabric to keep it in place, the Inspect-R® Density Gauge, application instructions and technical support. The system results in energy-efficient and comfortable homes for your customers since it:

**Will not corrode.** The PROPINK® Wall Insulation System does not require fire-retardant chemicals which can leach out, promoting corrosion of pipes, electrical equipment or structural metal attachments.

**Will not combust.** The PROPINK® Wall Insulation System meets all model building codes for noncombustibility.

**Is easy to install.** The PROPINK® Wall Insulation System fits easily into any shaped wall or ceiling cavity.

**Will not absorb moisture.** Moisture reduces insulation's effectiveness. The glass fibres in PROPINK® FIBERGLAS® Blown Insulation resist moisture buildup.

**Does not support mould growth.**† The PROPINK® Wall Insulation System does not support fungus or mould growth.

**Needs no wet adhesives.** The PROPINK® Wall Insulation System is a dry insulation system requiring no added water or adhesive.

**Virtually no settling, rot or deterioration with age.** With the PROPINK® Wall Insulation System, there's no danger of losing thermal resistance R/(rsi) over time.\*

**Reduces unwanted noise.** PROPINK® Wall Insulation System provides excellent isolation from unwanted exterior sounds.

### FOR CERTIFIED INSTALLERS ONLY

Only specially trained, professional contractors can install insulation using the PROPINK® Wall Insulation System. To find out about becoming certified, please contact your Area Sales Manager or call 1-800-GET-PINK® today.

### CONFORMS TO STANDARDS

The PROPINK® Wall Insulation System conforms to the product requirements of CAN/ULC S702, Type 5. The R-value stated on the label will be achieved when the product is installed according to label specifications. Its surface burning characteristics have been determined in accordance with CAN/ULC-S102.††

For loosefill and fabric:

- Flame Spread: <25
- Smoke Developed: <50

### INSULATION R-VALUE TABLE

Cavity Depth	Thermal Performance	Blown Density	Cavity Blown Weight/Area	Coverage/Bag	Bags/Area
mm (in) [stud]	RSI (R) Value*†	kg/m³ (lb/ft³)	kg/m² (lb/ft²)	m²/bag (ft²/bag)	bags/100m² (bags/1000ft²)
89 (3-1/2) [2x4]	2.55 (14.5)	22.4 (1.4)	1.99 (0.41)	7.52 (80.82)	13.29 (12.37)
140 (5-1/2) [2x6]	4.05 (22.7)	22.4 (1.4)	3.14 (0.64)	4.78 (51.43)	20.91 (19.44)
140 (5-1/2) [2x6]	4.23 (24)	33.6 (2.1)	4.70 (0.96)	3.19 (34.29)	31.36 (29.17)
184 (7-1/4) [2x8]	5.2 (29.8)	22.4 (1.4)	4.12 (0.85)	3.64 (39.01)	27.48 (25.63)
235 (9-1/4) [2x10]	6.7 (38.1)	22.4 (1.4)	5.26 (1.08)	2.85 (30.58)	35.09 (32.70)
286 (11-1/4) [2x12]	8.2 (46.4)	22.4 (1.4)	6.41 (1.31)	2.34 (25.14)	42.71 (39.77)
337 (13-1/4) [2x14]	9.6 (54.7)	22.4 (1.4)	7.55 (1.55)	1.99 (21.35)	50.33 (46.84)

\* Applications not covered by CCMC Evaluation Report # 13240-R are provided for applicator job estimation information. \*\*The higher the RSI or R-value, the greater the insulating power.

### PROPINK® COMPLETE™ FABRIC KEEPS INSULATION IN PLACE

PROPINK® Complete™ Nonwoven Fabric is a spunbound polypropylene material. It provides the insulation retention membrane for the PROPINK® Wall Insulation System.

PROPINK® Complete™ Nonwoven Fabric is designed to resist tearing and allows air but not glass fibres to pass through during the installation process. Because it's translucent, framing members are visible for easy application. It also allows for a convenient visual check when installing PROPINK® FIBERGLAS® Blown Insulation.

