

PROPINK® FIBERGLAS®

See CCMC Evaluation Report No. 12851-L

15 kg/33 lb bag

Blown Insulation

To obtain the thermal resistance shown on the chart, this material must be installed at both the thickness and mass per unit area equal to or greater than the minimum value specified.

PLEASE ENSURE THIS **PINK** INSTALLATION CARD IS PLACED PROMINENTLY IN YOUR ATTIC.

Thermal Resistance		Minimum Thickness ⁽¹⁾		Minimum Mass per Unit Area		Maximum Coverage per Bag ⁽²⁾		Minimum Number of Bags per Unit Area		Installation Record
RSI	R	mm	inches	kg/m²	lb/ft²	m²	ft²	100 m²	1000 ft ²	☐ Metric ☐ Imperial
2.1	12	112	4.5	0.90	0.184	16.7	179.7	6.0	5.6	Thermal Resistance Installed (RSI or R): Area Insulated (m² or ft²): Minimum Thickness (mm or inches):
2.8	16	150	6	1.20	0.245	12.5	134.8	8.0	7.4	
3.5	20	187	7.5	1.50	0.307	10.0	107.8	10.0	9.3	
4.2	24	225	9	1.80	0.368	8.3	89.9	12.0	11.1	
4.9	28	262	10.5	2.10	0.429	7.2	77.0	14.0	13.0	
5.6	32	299	12	2.40	0.491	6.3	67.4	16.0	14.8	
6.3	36	337	13.5	2.70	0.552	5.6	59.9	18.0	16.7	
7.0	40	374	14.75	2.99	0.613	5.0	53.9	20.0	18.5	
7.7	44	412	16.25	3.29	0.675	4.6	49.0	22.0	20.4	Calculated Number of Bags Required:
8.4	48	449	17.75	3.59	0.736	4.2	44.9	24.0	22.3	
8.8	50	468	18.5	3.74	0.767	4.0	43.1	25.0	23.2	
9.1	52	487	19.25	3.89	0.797	3.9	41.5	26.0	24.1	Number of Bags Installed:
9.8	56	524	20.75	4.19	0.859	3.6	38.5	28.0	26.0	
10.5	60	561	22.25	4.49	0.920	3.3	35.9	29.9	27.8	

Applicator (Company) Name:

Installer's Name:

Installer's Signature:

NOTES:

- (1) Measured in areas where thickness is not obstructed by roof slope or other obstructions
- (2) Coverage per bag may be increased 2% to 10% depending on joist spacings and depths using correction factors.
- (3) The applicator shall provide physical proof of the number of bags stated on this card by stapling in the immediate vicinity of this card, the approximately 3" x 3" Owens Corning logos cut from all bags used on this job.

Date.

OWENS CORNING CANADA LP 3450 McNicoll Avenue Scarborough, Ontario M1V 1Z5

1-800-GET-PINK® www.owenscorning.ca