

WINDOW, DOOR & SIDING

OSI[®]

QUAD[®]

ADVANCED FORMULA SEALANT



QUAD[®]
ADVANCED FORMULA SEALANT

- All-weather formula
- Permanently flexible
- Primerless adhesion
- For wet or dry surfaces
- Will not crack or yellow
- Paintable/stainable
- Mildew resistant
- Available in clear, white and over 240 colors
- Clear goes on clear and stays clear
- New Break-A-Way™ Seal inside every nozzle
- VOC compliant

QUAD® Window, Door & Siding Sealant originally was developed for vinyl siding and window applications, this product is ideal for use in many window, door & siding projects where water and weather-tight seals are required.

Quad is recommended for use on porous and non-porous building materials for exterior applications on vinyl, aluminum, steel, copper, fiber-cement, stucco, most masonry, fiberglass, cedar and composite wood building materials.



PHYSICAL PROPERTIES

Type	Elastomeric polymers
Color	Clear (colors optional)
Solids by Weight	75% colors, 65% clear
Net weight / gal.	7.5 lbs. / gal.
Flash Point	0° F
Flammability	Flammable (see cartridge caution)
Toxicity	Refer to MSDS
Open Time*	5-10 minutes
Cure Time	Approximately 7 days
Application Temperature	20 F to 100° F
Service Temperature	-20° F to 200° F
Joint Movement Capability	25% typical
Freeze-Thaw Stability	Will not freeze
Shelf Life	18 months from date of manufacture
Clean Up	Mineral spirits or paint thinner
VOC Level	Refer to MSDS

*NOTE: Open time can vary due to prevailing environmental conditions present at time of application, such as temperature, humidity and wind velocity.

**For fast, smooth, easy application during cold weather, sealant should be kept at room temperature 24 hours prior to use.

SPECIFICATIONS

Conforms to the performance characteristics of: Federal Spec. TT-S-00230C; TT-S-001657 Type 1; ASTM C 920, Type S, NS, NT; AAMA 1407.1-78; AAMA 803.3-92

FEATURES

- Excellent stretch & movement capability
- Goes on smoothly, with easy cut-off
- Does not collect dirt
- No tooling required
- Excellent UV resistance
- Cures to a tough, long-lasting seal
- Elastomeric

LIMITATIONS

- Not recommended for interior applications
- Not recommended for traffic bearing surfaces
- Not recommended for use in swimming pools or fish tanks
- Not intended for total roof resurfacing projects
- Not recommended for expansion joints
- Not recommended for log homes
- Do not use on polystyrene foam or panels
- Do not use on field or butt joints on fiber cement siding

PACKAGING

10.2 oz (301 ml) cartridges w/4" spout; 12 per case
 Available in white, clear and over 240 colors matched to the most popular siding manufacturers

10.2 oz (301 ml) cartridges w/3" spout; 12 per case
 Available in white or clear only.
 Please specify 3" or 4" spout when placing orders.
 Contact Henkel customer service for color cross reference.

COVERAGE

3/8" bead, approximately 14 lin. ft. per 10.2 oz.

FOR COMMERCIAL USE, CONTACT OSI SEALANTS TECHNICAL DEPARTMENT

For more information contact Henkel at phone: 800-624-7767, fax: 440-255-1008, and request the QUAD Technical Data Sheet or visit our website: www.osiproseries.com



Henkel Corporation
 Professional and Consumer Adhesives
 Mentor, Ohio 44060