

MATERIAL SAFETY DATA SHEET

MSDS Name: OSI TeQ:: FLASH Flexible Window Flashing
MSDS Number: 00-98872
Version Number
Revision Date: JAN-18-2007
Page Number: 1

SECTION I - PRODUCT AND COMPANY INFORMATION

Product Name: OSI TeQ:: FLASH Flexible Window Flashing
HMIS Hazard Rating: Health: 2 Fire: 0 Reactivity: 0 PPE:

Company Identification: HENKEL CORPORATION
7405 PRODUCTION DRIVE
MENTOR OH 44060

Contact (24 hour): Customer Affairs (800)321-0253
Information phone/Fax: (440) 255-8900 / (440) 974-8358
CHEMTREC Emergency (24 hour): (703) 527-3887 (International)
(800) 424-9300
in Canada CANUTEK 613-996-6666

Product Class VAPOR BARRIER
Trade Name OSI WIN TeQ
Product Code See No. above

SECTION II - INGREDIENT AND HAZARD INFORMATION

Hazardous Ingredient Name	CAS Number	Percent	TSCA
PETROLEUM ASPHALT *	64742-93-4	60 - 80	Y
AROMATIC OIL	64742-05-8	10 - 15	Y

Ingredient Notes:
Remaining ingredients are not considered OSHA hazardous.

SECTION III - PHYSICAL AND CHEMICAL PROPERTIES

Form: ASPHALT TAPE
Appearance/Color: BLACK
pH Value, +/- .3: Not Applicable
Boiling Range: Not Applicable
Vapor Pressure (mmHg): Not Applicable
Evaporation Rate: Non Volatile

Vapor Density: Non Volatile

% Volatile, Weight Not Applicable
% Volatile, Volume 0.%

MATERIAL SAFETY DATA SHEET

MSDS Name: OSI TeQ:: FLASH Flexible Window Flashing
MSDS Number: 00-98872
Version Number
Revision Date: JAN-18-2007
Page Number: 2

Specific Gravity: 1.179
VOC (less H2O or exempt) NONE

SECTION IV - FIRE FIGHTING MEASURES

Flammability Class
Flash Point: Not Applicable
Explosive Range (LEL/UEL): 0.%
0.%

EXTINGUISHING MEDIA:

Carbon Dioxide---Dry Chemical---Foam--Sand

SPECIAL FIRE-FIGHTING PROCEDURES:

Use self-contained breathing apparatus with full facepiece
operated in pressure demand or other positive pressure mode.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

None

SECTION V - HEALTH HAZARD DATA

Route	Species	Exposure and Dose
-------	---------	-------------------

EFFECTS OF OVEREXPOSURE

Inhalation: May cause nose or throat irritation.
Skin/Eye Contact: May cause irritation.
Ingestion: Swallowing large amounts may cause nausea,
vomiting. (an unlikely route of entry)

FIRST AID MEASURES

Inhalation: If affected by inhalation, remove to fresh air.
Eye Contact: Flush with water for at least 15 minutes, and
get prompt medical attention.
Skin Contact: Wash skin thoroughly with soap and water.
Ingestion: Drink water, and get medical attention.

N/A= Not applicable N/AV=Not available N/E, N/est=Not established

CHRONIC HAZARDS

Repeated contact with rubberized asphalt may result in slight
irritation.
Prolonged or repeated contact with Process Oil in the rubberized
asphalt may cause an increased risk of skin cancer and liver damage
based on laboratory animal tests. Skin cleansing studies with aromatic
oils show that toxic effects are not likely to occur if good personal
hygiene practices are used.

MATERIAL SAFETY DATA SHEET

MSDS Name: OSI TeQ:: FLASH Flexible Window Flashing
MSDS Number: 00-98872
Version Number
Revision Date: JAN-18-2007
Page Number: 3

SECTION VI - STABILITY AND REACTIVITY

Stability: Product is stable under normal storage conditions
Hazardous Polymerization: Will not occur under normal conditions

INCOMPATIBILITY:

None

CONDITIONS TO AVOID:

None

HAZARDOUS DECOMPOSITION PRODUCTS:

May produce oxides of carbon and oxides of nitrogen when burned.

SECTION VII - ACCIDENTAL RELEASE AND DISPOSAL MEASURES:

STEPS TO BE TAKEN IN CASE OF SPILL:

Cold material may be picked up by hand, non-hazardous.

WASTE DISPOSAL METHOD:

Dispose of in accordance with Federal, State, and Local regulations.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

Table with 5 columns: ACGIH TLV, ACGIH TLV-C, ACGIH STEL, OSHA STEL, OSHA PEL. Rows include PETROLEUM ASPHALT * and AROMATIC OIL.

VENTILATION:

Local exhaust is recommended for safe practice.

PROTECTIVE CLOTHING:

Gloves and clothing should be worn to prevent repeated skin contact.

EYE PROTECTION:

Eye protection should be worn.

HANDLING AND STORAGE PRECAUTIONS:

Keep away from heat (over 100F), or flame
Keep out of the reach of children
Do not take internally.
Avoid prolonged or repeated contact with skin.

SECTION IX - TRANSPORT INFORMATION: (not all sizes available)

MATERIAL SAFETY DATA SHEET

MSDS Name: OSI TeQ:: FLASH Flexible Window Flashing
MSDS Number: 00-98872
Version Number
Revision Date: JAN-18-2007
Page Number: 4

GROUND TRANSPORT (DOT) - DOMESTIC

- NON-REGULATED

AIR TRANSPORT (DOT) - DOMESTIC

- NON-REGULATED

SECTION X - REGULATORY INFORMATION:

-PROP 65 (CARCINOGEN)

WARNING: This product contains a chemical known to the state of California to cause cancer.

Ingredient Name	CAS Number	Percent
PETROLEUM ASPHALT *	64742-93-4	60 - 80

SARA Section 311/312 Hazard Categories met:
Immediate (Acute) and Delayed (Chronic) Health Hazards
Chemical substances are TSCA listed.

DISCLAIMER:

The information contained herein is based on data available as of the date of preparation of this MSDS and which we believe to be reliable. However, no warranty is expressed or implied regarding the accuracy of the data. We shall not be responsible for the use of this information, or of any product, method, apparatus mentioned, and user must make his own investigation to determine the suitability of the information or products for his particular purpose, for the protection of the environment, and the health & safety of the users of this material.