Material Safety Data Sheet



Revision Number: 002.0 Issue date: 03/30/2011

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: OSI TeQ::Seal Window Flange Sealant IDH number: 1003802

Product type: Sealant

Region: United States

Company address:Contact information:Henkel CorporationTelephone: 800.624.7767

One Henkel Way

Rocky Hill, Connecticut 06067

MEDICAL EMERGENCY Phone: Poison Control Center
1-877-671-4608 (toll free) or 1-303-592-1711
TRANSPORT EMERGENCY Phone: CHEMTREC

1-800-424-9300 (toll free) or 1-703-527-3887

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HMIS:

Physical state:PasteHEALTH:*2Color:whiteFLAMMABILITY:1Odor:alcohol-likePHYSICAL HAZARD:0

Personal Protection: See MSDS Section 8
WARNING: PROLONGED OR REPEATED CONTACT WITH UNCURED SEALANT MAY

CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.

Relevant routes of exposure: Inhalation, Skin contact, Eye contact

Potential Health Effects

Inhalation: May be harmful if inhaled. Methanol is released during application and cure, which may affect

the nervous system causing dizziness, headache or nausea.

Skin contact: Prolonged or repeated contact with uncured sealant may cause skin irritation.

Eye contact: Vapors may irritate eyes. Contact with eyes will cause irritation.

Ingestion: Harmful if swallowed. Not expected under normal conditions of use.

Existing conditions aggravated by

exposure:

Eye, skin, and respiratory disorders.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR

1910.1200).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
1,2-Benzenedicarboxylic acid, diundecyl ester, branched and linear	85507-79-5	10 - 30
Limestone	1317-65-3	10 - 30
Titanium dioxide	13463-67-7	1 - 5
Trimethoxyvinylsilane	2768-02-7	1 - 5
Methanol	67-56-1	0 - 0.1

Exposure to moisture during cure will release 1-2% methanol.

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If symptoms persist, seek medical advice.

Skin contact: Wash with soap and water. If skin irritation persists, call a physician. Wipe off

paste with paper towel or cloth.

Eye contact: Rinse thoroughly with plenty of water, also under the eyelids. If eye irritation

persists, consult a specialist.

Ingestion: Do not induce vomiting. If a person feels unwell or symptoms of skin irritation

appear, consult a physician.

Notes to physician:Treat symptomatically.

5. FIRE FIGHTING MEASURES

Flash point: Not applicable

Autoignition temperature: Not available

Flammable/Explosive limits - lower: Not available

Flammable/Explosive limits - upper: Not available

Extinguishing media: Foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear.

Unusual fire or explosion hazards: None

Hazardous combustion products: Oxides of carbon. Oxides of silicon. calcium oxide

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:Do not allow product to enter sewer or waterways.

Clean-up methods: Store in a partly filled, closed container until disposal. Spilled material will

solidify. Scrape up as much material as possible. Maintain good ventilation for

large spills.

7. HANDLING AND STORAGE

Handling: Do not handle contact lenses until all sealant has been removed from hands.

Residual sealant may transfer to lenses and cause eye irritation. Avoid contact with eyes, skin and clothing. Keep out of the reach of children. Protect from

moisture.

Storage: Keep container closed. Store in a dry area below 90° F.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

IDH number: 1003802 Product name: OSI TeQ::Seal Window Flange Sealant

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
1,2-Benzenedicarboxylic acid, diundecyl ester, branched and linear	None	None	None	None
Limestone	10 mg/m3 TWA Total dust.	5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust.	None	None
Titanium dioxide	10 mg/m3 TWA	15 mg/m3 TWA Total dust.	None	None
Trimethoxyvinylsilane	None	None	None	None
Methanol	200 ppm TWA (SKIN) 250 ppm STEL	200 ppm (260 mg/m3) TWA	None	None

Engineering controls: Ensure adequate ventilation, especially in confined areas.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

limit(s).

Eye/face protection: Safety goggles or safety glasses with side shields.

Skin protection: Chemical resistant, impermeable gloves. Neoprene, Butyl-rubber, or nitrile-

rubber gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Paste Color: white Odor: alcohol-like Odor threshold: Not available pH: Not available Vapor pressure: Not available Boiling point/range: Not available Melting point/ range: Not available Specific gravity: 1.388 at 20 °C (68°F) Vapor density: Heavier than air. Flash point: Not applicable Flammable/Explosive limits - lower: Not available Flammable/Explosive limits - upper: Not available Not available Autoignition temperature: **Evaporation rate:** Not available Solubility in water: Insoluble Partition coefficient (n-octanol/water): Not available VOC content: < 3 %; 21 g/l

10. STABILITY AND REACTIVITY

Stability: Not available

Hazardous reactions: Will not occur.

Hazardous decomposition products: Oxides of carbon. Oxides of silicon. Calcium oxide. Methanol is liberated

slowly upon exposure to moisture.

Incompatible materials: Oxidizing agents. Water Acids. Alkalis.

Conditions to avoid: Exposure to moisture.

IDH number: 1003802

11. TOXICOLOGICAL INFORMATION

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
1,2-Benzenedicarboxylic acid, diundecyl ester, branched and linear	No	No	No
Limestone	No	No	No
Titanium dioxide	No	Group 2B	No
Trimethoxyvinylsilane	No	No	No
Methanol	No	No	No

Hazardous components	Health Effects/Target Organs	
1,2-Benzenedicarboxylic acid, diundecyl ester, branched and linear	No Records	
Limestone	Nuisance dust	
Titanium dioxide	Irritant, Respiratory, Some evidence of carcinogenicity	
Trimethoxyvinylsilane	Irritant, Allergen	
Methanol	Eyes, Heart, Irritant, Kidney, Liver, Metabolic, Nervous System, Reproductive	

12. ECOLOGICAL INFORMATION

Ecological information: Not available

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: It is the responsibility of the user to determine if an item is hazardous as

defined in the Resource Conservation and Recovery Act (RCRA) at the time of disposal. Product uses, transformations, mixtures, processes, etc., may render the resulting material hazardous, under the criteria of ignitability, corrosivity, reactivity and toxicity characteristics of the Toxicity Characteristics

Leaching Procedure (TCLP) 40 CFR 261.20-24.

14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:Not regulatedHazard class or division:NoneIdentification number:NonePacking group:None

International Air Transportation (ICAO/IATA)

Proper shipping name:Not regulatedHazard class or division:NoneIdentification number:NonePacking group:None

Water Transportation (IMO/IMDG)

Proper shipping name:
Hazard class or division:
Identification number:
Packing group:

Not regulated
None
None
None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

IDH number: 1003802 Product name: OSI TeQ::Seal Window Flange Sealant

TSCA 12(b) Export Notification: None above reporting de minimus

CERCLA/SARA Section 302 EHS:
CERCLA/SARA Section 311/312:
CERCLA/SARA 313:

None above reporting de minimus
Delayed Health, Immediate Health
None above reporting de minimus

California Proposition 65: This product contains a chemical known in the State of California to cause cancer.

Canada Regulatory Information

IDH number: 1003802

CEPA DSL/NDSL Status: One or more components are not listed on, and are not exempt from listing on either the

Domestic Substances List or the Non-Domestic Substances List.

WHMIS hazard class: D.2.A, D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format

Prepared by: Mary Ellen Roddy, Sr. Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

Product name: OSI TeQ::Seal Window Flange Sealant