

## Product Data

# VIPER VENT™

A Ridge Vent for a Durable Roof



### Description

VIPER VENT™ is a patented, light weight, ridge vent that provides an industry leading 15 square inches of net free vent area per liner foot (15 in<sup>2</sup>/LF). Our one of a kind double density edge provides superior strength and rigidity, ensuring its ability to maintain a sleek finished look that makes it virtually invisible.

Additionally, Viper Vents filter is manufactured with extra thick fibers, the UV resistant textile is 40% thicker than the industry standard allowing VIPER VENT to provide superior air flow over its lifetime.

Viper Vent is manufactured in 5 versions: 20 LF, 20 LF with nails, and 50 LF, 50 LF with nails, and a 4 ft stick. All versions meet the needs of your local building code. VIPER VENT offers 15 in<sup>2</sup>/LF Net Free Ventilation Area (NFVA).

### Applications

- ✓ Asphalt roof
- ✓ Wood roof
- ✓ Tile roof
- ✓ Metal roof
- ✓ Slate roof

*For FULL VERSION of Ridge/Hip Installation Instructions please see document: KC-02001*

### Features and Benefits

Designed with ultra-low profile, nearly invisible when installed

Superior edge strengthen for uniform installation

Easily centered on the ridge

Lightweight and easy to install

Available in a variety of widths and lengths

### Properties

Description	Measurement	
Core Polymer	Nylon	
<b>Width for 11"</b>	11.0 in.	279.4 mm
<b>Width for 9"</b>	9.0 in.	228.6 mm
<b>Width for 7"</b>	7.0 in.	177.8 mm
Thickness	0.625 in.	15.9 mm
Weight of Core	2.0 oz/ft <sup>2</sup> ( 56.7g/31cm <sup>2</sup> )	
NFVA	15 in <sup>2</sup> /LF	

## Packaging

Product Name	Product Part Number	Rolls per Unit	Units per Truck	Weight per Roll WO Nails		Weight per Roll With Nails		Length per Roll	
				lb	kg	lb	kg	ft	m
11" VIPER VENT 20 with nails 11" VIPER VENT 20 without nails	VV-11-20-N VV-11-20	72	26	3.2	1.45	3.9	1.77	20	6.1
11" VIPER VENT 50 with nails 11" VIPER VENT 50 without nails	VV-11-50-N VV-11-50	32	26	8.0	3.63	8.7	3.95	50	15.24
11" VIPER VENT 4 without nails	VV-11-04	12	26	15.8	7.17			80 <sup>1</sup>	24.38 <sup>1</sup>
9" VIPER VENT 20 with nails 9" VIPER VENT 20 without nails	VV-09-20-N VV-09-20	90	26	3.0	1.36	3.7	1.68	20	6.1
9" VIPER VENT 50 with nails 9" VIPER VENT 50 without nails	VV-09-50-N VV-09-50	40	26	7.5	3.4	8.2	3.72	50	15.24
7" VIPER VENT 20 with nails 7" VIPER VENT 20 without nails	VV-07-20-N VV-07-20	108	26	2.6	1.17	3.3	1.5	20	6.1
7" VIPER VENT 50 with nails 7" VIPER VENT 50 without nails	VV-07-50-N VV-07-50	48	26	8.06	3.66	8.76	3.97	50	15.24

<sup>1</sup> - 11" VIPER VENT 4 is packaged in a box. Length represents total amount per box.

LIMITED WARRANTY: Keene Building Products, Inc. warrants to the initial purchaser only that the goods sold hereunder will be free from defects in material and workmanship and, except as otherwise set forth herein, will conform to the specifications provided. If any failure to meet this warranty appears within one year from the date of shipment of the goods, on the condition that Keene Building Products, Inc. will correct any such failure by either replacing or repairing any defective goods, at Keene Building Products, Inc.'s option.

The preceding paragraph sets forth the exclusive remedy for all claims based on failure of or defect in the goods sold hereunder, whether such failure or defect arises before or during the warranty period and whether a claim, however instituted, is based on contract, indemnity, warranty, tort (including negligence), strict liability or otherwise. The foregoing warranty is exclusive and is in lieu of all other warranties whether written, oral, implied or statutory.