

Small. High-Powered. Economical.



Venmar AVS introduces the new K Series.

The Kubix products are gaining popularity since their arrival on the market. We are now expanding the range by offering products providing up to 95 CFM.

The Ideal Air Exchanger for Small Spaces




The K Series is the ideal choice for condominiums, apartments and other limited space applications that require up to 95 CFM of continuous ventilation. With their compact size and 4-inch ports, they can be installed in small spaces such as a closet or mechanical room above a hot water tank.

- Now offering up to 95 CFM airflow to cover ventilation needs of larger homes
- Advanced blower design for quiet operation
- Fast and easy installation with top or side ports options
- Meet ENERGY STAR® requirements
- Easy to balance with integrated dampers and pressure taps
- Now with a 5-year warranty

ENERGY STAR® and NOVOCLIMAT 2.0* compliant!

In addition to being ENERGY STAR® qualified, the K8 and K10 units are specifically designed to fulfill all your residential ventilation needs and to meet the characteristics of an air exchanger in the efficient home programs.



Specifications	K7 HRV	K7 ERV	K8 HRV	K10 HRV
Part number	44150	44162 (Top ports) 44163 (Side ports)	44152 (Top ports) 44153 (Side ports)	44500 (Top ports) 44502 (Side ports)
Maximum continuous air flow (at 0.2 in. w.g.)	79 CFM	78 CFM	86 CFM	95 CFM
Maximum continuous air flow (at 0.4 in. w.g.)	71 CFM	70 CFM	77 CFM	90 CFM
Sensible Recovery Efficiency @ 0°C	55% @ 36 CFM	66% @ 35 CFM	66% @ 47 CFM	66% @ 47 CFM
Sensible Recovery Efficiency @ -25°C	55% @ 38 CFM	56% @ 36 CFM	60% @ 48 CFM	60% @ 48 CFM
Total Recovery Efficiency @ 35°C	n/a	50% @ 36 CFM	n/a	n/a
Dimensions	Height: 16.3 in. (41.1 cm) • Width: 15.5 in. (39.4 cm) • Depth: 15.6 in. (39.6 cm)			
Pressure taps to balance air flow	No	Yes	Yes	Yes
Balancing dampers	No	Yes	Yes	Yes
Fan efficacy	0.9 CFM/W	1.0 CFM/W	1.2 CFM/W	1.2 CFM/W
Electrical consumption (low speed)	40 W	34 W	36 W	38 W
Wall control compatibility	Dehumidistat (included)	Deco-Touch, Altitude, Lite-Touch, Constructo, Simple-Touch	Deco-Touch, Altitude, Lite-Touch, Constructo, Simple-Touch	Deco-Touch, Altitude, Lite-Touch, Constructo, Simple-Touch
Warranty on parts	5 years	5 years	5 years	5 years
Warranty on core	Limited lifetime	5 years	Limited lifetime	Limited lifetime
 	Yes	Yes	Yes	Yes
	No	No	Yes	Yes
*Meet Novoclimat™ 2.0 program requirements in Quebec, Canada	No	No	Yes	Yes

These specifications are subject to change without notice, please see the specification sheet on www.venmar.ca.

Available at this authorized dealer:



Venmar Ventilation Inc., Residential Group
550 Lemire Blvd., Drummondville (Quebec) Canada J2C 7W9
Toll-Free: 1-800-567-3855 (Canada and USA)

www.venmar.ca