

Small. High-Powered. **Economical.**

The Ideal Air Exchanger for Small Spaces.

- Low cost
- Minimal space required
- Very quiet operation
- Quick and easy to install



Perfection in a cube!



- Integrated hooks
- Chain and spring kit included
- Optional wall mount bracket
- Integrated drain fitting to ease installation



KUBIX

- From only 30 lb (13.6 kg)
- 4-inch round ports
- Venmar quality

- Quick and easy to balance
- Quiet and efficient blower (Patent pending)

	Line Contraction	Line Line	HARE HARE
Specifications	HRV	HRV Plus	ERV
Part number	44100 (Top Ports)	44102 (Top Ports) 44103 (Side Ports)	44112 (Top Ports) 44113 (Side Ports)
Maximum continuous air flow (at 0.4" pressure)	70 cfm	70 cfm	70 cfm
Minimum continuous air flow (at 0.4" pressure)	35 cfm	35 cfm	35 cfm
Sensible Recovery Efficiency @ 0°C (35 cfm nominal)	55%	67%	66%
Sensible Recovery Efficiency @ 0°C (64 cfm nominal)	48%	61%	60%
Sensible Recovery Efficiency @ -25°C (35 cfm nominal)	53%	58%	56%
Total Recovery Efficiency at 35°C	n/a	n/a	50%
Dimensions	Height: 16.3"	(41.4 cm) • Width: 15.5" (39.4 cm) •	Depth: 15.6" (39.6 cm)
Pressure taps to balance air flow	No	Yes	Yes
Balancing dampers	No	Yes	Yes
Electrical consumption (low speed)	1 cfm/watt	More than 1 cfm/watt	1 cfm/watt
Wall control compatibility	20 min Push Button, Dehumidistat (included)	Deco-Touch, Altitude, Lite Touch, Constructo, Dehumidistat, 20 min Push Button	Deco-Touch, Altitude, Lite Touch, Constructo, Dehumidistat, 20 min Push Button
Warranty on parts	2 years	2 years	2 years
Warranty on core	Limited lifetime	Limited lifetime	5 years
	Yes	Yes	Yes
Burrfill Baller State Baller State	No	Yes	Yes
Meets Novoclimat [™] program requirements	No	Yes	Yes

These specifications are subject to change without notice, please see the specification sheet on www.venmar.ca.

Available at this authorized dealer:



Venmar Ventilation Inc., Residential Group 550, Lemire Blvd., Drummondville (Quebec) Canada J2C 7W9 Toll-Free: 1-800-567-3855 (Canada and USA)

www.venmar.ca