# Accella Polyurethane Systems Safety Data Sheet

# 1. Identification of Substance:

Product Name: BAYSEAL CC XP (84046117)

Supplier Identification: Telephone: (281) 350-9000

Accella Polyurethane Systems

Address: 2400 Spring Stuebner Rd.

Spring, TX 77389

24-Hr. Emergency Phone Number:

CHEMTREC (800) 424-9300 International: (703) 527-3887

Product Use: Polyurethane polyol component

## 2. Hazards Identification

#### **GHS Ratings:**

| Skin corrosive     | 2  | Reversible adverse effects in dermal tissue, Draize score: >= |
|--------------------|----|---|
|                    |    | 2.3 < 4.0 or persistent inflammation                          |
| Eye corrosive      | 1  | Serious eye damage: Irreversible damage 21 days after         |
|                    |    | exposure, Draize score: Corneal opacity >= 3, Iritis > 1.5    |
| Skin sensitizer    | 1  | Skin sensitizer   |
| Reproductive toxin | 1B | Presumed, Based on experimental animals                       |
|                    | •  |   |

Organ toxin repeated 2 Presumed to be harmful to human health- Animal studies exposure with significant toxic effects relevant to humans at generally

moderate exposure (guidance)- Human evidence in

exceptional cases

#### **GHS Hazards**

H315

| H317 | May cause an allergic skin reaction                               |
|------|---|
| H318 | Causes serious eye damage   |
| H360 | May damage fertility or the unborn child                          |
| H373 | May cause damage to organs through prolonged or repeated exposure |

Causes skin irritation

# **GHS Precautions**

P302+P352

| recautions |   |
|------------|---|
| P201       | Obtain special instructions before use                                    |
| P202       | Do not handle until all safety precautions have been read and understood  |
| P260       | Do not breathe dust/fume/gas/mist/vapours/spray                           |
| P261       | Avoid breathing dust/fume/gas/mist/vapours/spray                          |
| P264       | Wash hands thoroughly after handling                                      |
| P272       | Contaminated work clothing should not be allowed out of the workplace     |
| P280       | Wear protective gloves/protective clothing/eye protection/face protection |
| P281       | Use personal protective equipment as required                             |
| P310       | Immediately call a POISON CENTER in case of overexposure.                 |
| P314       | Get Medical advice/attention if you feel unwell                           |
| P321       | Specific treatment is urgent (see Section 4 First Aid measures)           |
| P362       | Take off contaminated clothing and wash before reuse                      |
| P363       | Wash contaminated clothing before reuse                                   |
|            |   |

IF ON SKIN: Wash with soap and water

SDS for: BAYSEAL CC XP Page 1 of 6

P305+P351+P338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact

lenses if present and easy to do - continue rinsing

P308+P313 IF exposed or concerned: Get medical advice/attention P332+P313 If skin irritation occurs: Get medical advice/attention

P333+P313 If skin irritation or a rash occurs: Get medical advice/attention

P405 Store locked up

P501 Dispose of contents/container in accordance with Section 13

Signal Word: Danger





# 3. Composition/Data on Components:

| Chemical Name  | CAS number  | Weight Concentration % |
|--|-------------|------------------------|
| Oxirane, 2-methyl-, polymer with oxirane, ether with 2,6-bis [[bis(2-hydroxyethyl)amino]methyl]-4-branched nonylphenol | 940912-28-7 | 10.00-20.00%           |
| 1,1,1,3,3-Pentafluoropropane   | 460-73-1    | 10.00-20.00%           |
| 2-Propanol, 1-chloro-, phosphate (3:1)   | 13674-84-5  | 1.00-5.00%             |
| .alphaD-Glucopyranoside, .betaD-fructofuranosyl, polymer with methyloxirane and oxirane                                | 26301-10-0  | 1.00-5.00%             |
| Diethylene glycol  | 111-46-6    | 1.00-5.00%             |
| 2-Propanol, 1-[bis[3-(dimethylamino)propyl]amino]-   | 67151-63-7  | 1.00-5.00%             |
| 2-Butoxyethanol  | 111-76-2    | 1.00-5.00%             |
| Ethylene oxide, polymer with 2,2'-iminodiethanol and propylene oxide   | 34354-45-5  | 1.00-5.00%             |

#### 4. First Aid Measures:

**Inhalation:** If inhaled and symptoms ensue, move to fresh air. If breathing is difficult, give oxygen.

After Eye Contact: Rinse opened eye for at least 15 minutes under running water.

Remove contact lenses if present and easy to do so, and continue rinsing. If irritation persists contact

physician

After Skin Contact: Clean affected area with soap and plenty of water.

After Swallowing: Do not induce vomitting. Consult physician.

Notes to Physician: Treat symptomatically

#### 5. Fire Fighting Measures:

Flash Point: >212°, 100°C

LEL: N/A UEL: N/A

Upper and Lower Explosive Limits listed if known.

Suitable Extinguishing Agents: Water spray, CO2, Foam, Dry chemical

Information about Protection against Explosions and Fires: Closed containers may

SDS for: BAYSEAL CC XP Page 2 of 6

rupture when exposed to extreme heat.

Dangerous Products of Decomposition: Oxides of carbon, oxides of nitrogen, oxides of phosphorus, hydrocarbons, traces of HCN, hydrogen chloride gas, hydrogen fluoride

## 6. Accidental Release Measures:

Person-Related Safety Precautions: Avoid contact with skin and eyes.

**Measures for Environmental Protection:** Cover and contain spill with absorbent material. Collect for proper disposal according to local, state, and federal regulations. Use appropriate personal protective equipment during clean up. Evacuate and keep unnecessary people out of spill area.

# 7. Handling and Storage:

**Information for Safe Handling:** Avoid contact with skin or inhalation.

**Storage Requirements:** Store in dry, well ventilated area. Keep containers tightly closed. Store between 60°F-100°F. Material may settle.

#### 8. Exposure Controls and Personal Protection:

| Chemical Name / CAS No.  | OSHA Exposure Limits         | ACGIH Exposure Limits | Other Exposure Limits             |
|--|------------------------------|-----------------------|-----------------------------------|
| Oxirane, 2-methyl-, polymer with oxirane, ether with 2,6-bis[[bis(2-hydroxyethyl) amino]methyl]-4-branched nonylphenol 940912-28-7 | Not Established              | Not Established       | Not Established                   |
| 1,1,1,3,3-Pentafluoropropane<br>460-73-1   | Not Established              | Not Established       | Not Established                   |
| 2-Propanol, 1-chloro-,<br>phosphate (3:1)<br>13674-84-5  | Not Established              | Not Established       | Not Established                   |
| .alphaD- Glucopyranoside, .betaD- fructofuranosyl, polymer with methyloxirane and oxirane 26301-10-0                               | Not Established              | Not Established       | Not Established                   |
| Diethylene glycol<br>111-46-6  | Not Established              | Not Established       | Not Established                   |
| 2-Propanol, 1-[bis[3-<br>(dimethylamino)propyl]<br>amino]-<br>67151-63-7   | Not Established              | Not Established       | Not Established                   |
| 2-Butoxyethanol<br>111-76-2  | 50 ppm TWA; 240 mg/m3<br>TWA | 20 ppm TWA            | NIOSH: 5 ppm TWA; 24<br>mg/m3 TWA |
| Ethylene oxide, polymer with 2,2'-iminodiethanol and propylene oxide 34354-45-5  | Not Established              | Not Established       | Not Established                   |

SDS for: BAYSEAL CC XP Page 3 of 6

Printed: 3/20/2017 at 10:40:21AM

**Engineering Controls:** No specific measures required. If spraying mixed with isocyanate component refer to that SDS for exposure limits and recommended exhaust ventiliation.

**General Protective and Hygienic Measures:** Usual precautionary measures should be adhered to when handling chemicals.

**Respiratory protection:** None required if work area is properly ventilated.

**Hand Protection:** Protective chemical resistant gloves.

Eye Protection: Safety glasses.

Body Protection: Protective work clothing. Launder separately.

#### 9. Physical and Chemical Properties:

Physical properties listed where known.

Appearance: Amber liquid Odor: Mild

Vapor Pressure: N/A

Vapor Density: N/A

pH: N/A

Density: 1.00 Melting point: N/A

Freezing point: N/A Solubility: N/A Flash

Boiling range: 15 - 342°C point: >212°F,100°C

Evaporation rate: N/A Flammability: N/A

Explosive Limits: N/A Partition coefficient (n- N/A octanol/water):

Autoignition temperature: 229°C Decomposition temperature: N/A

# 10. Stability and Reactivity:

Chemical Incompatible Materials: Avoid contact with isocyanates and strong oxidizing agents.

Hazardous Polymerization: Not expected to occur.

**Dangerous Products of Decomposition:** Oxides of carbon, oxides of nitrogen, oxides of phosphorus, hydrocarbons, traces of HCN, hydrogen chloride gas, hydrogen fluoride

#### 11. Toxicological Information:

#### **Mixture Toxicity**

Oral Toxicity LD50: 3,507mg/kg Dermal Toxicity LD50: 1,250mg/kg Inhalation Toxicity LC50: 66mg/L

#### **Component Toxicity**

13674-84-5 2-Propanol, 1-chloro-, phosphate (3:1)

Oral LD50: 500 mg/kg (Rat) Dermal LD50: 1,230 mg/kg (Rabbit) Inhalation LC50: 5 mg/L (Rat)

111-76-2 2-Butoxyethanol

Oral LD50: 470 mg/kg (Rat) Dermal LD50: 1,250 mg/kg (Rabbit) Inhalation LC50: 450 ppm (Rat)

# **Individual Toxicity Values Listed if Known**

#### **Acute Toxicity:**

SDS for: BAYSEAL CC XP Page 4 of 6

Eyes: Irritating to eyes

Skin: Harmful in contact with skin

**Inhalation:** Not expected to be a route of exposure **Ingestion:** Harmful if swallowed. Consult physician

Chronic Effects: Possible harmful target organ effects

Routes of Entry: Ingestion, skin contact, eye contact

Target Organs: Skin, eyes, digestive tract

**Chemicals with Known or Possible Carcinogenic Effects:** 

CAS NumberDescription% WeightCarcinogen RatingNoneNo data available

#### 12. Ecological Information:

**General Information:** Based on experience, no adverse effects are to be expected if correct disposal procedures have been followed as indicated in section 13. Individual component ecotoxicity listed if known.

#### **Component Ecotoxicity**

2-Propanol, 1-chloro-, phosphate 96 Hr LC50 Brachydanio rerio: 56.2 mg/L [static]; 96 Hr LC50 Pimephales

(3:1) promelas: 98 mg/L [static]; 96 Hr LC50 Poecilia reticulata: 30 mg/L [static]

48 Hr EC50 Daphnia magna: 63 mg/L

72 Hr EC50 Desmodesmus subspicatus: 45 mg/L; 96 Hr EC50

Pseudokirchneriella subcapitata: 4 mg/L

Diethylene glycol 96 Hr LC50 Pimephales promelas: 75200 mg/L [flow-through]

48 Hr EC50 Daphnia magna: 84000 mg/L

2-Butoxyethanol 96 Hr LC50 Lepomis macrochirus: 1490 mg/L [static]; 96 Hr LC50 Lepomis

macrochirus: 2950 mg/L

48 Hr EC50 Daphnia magna: >1000 mg/L

#### 13. Disposal Considerations:

**Recommendation:** Observe local requirements. Dispose of in accordance with local/state/federal regulations.

**Empty Container Precautions:** Recondition or dispose of empty container in accordance with governmental regulations. If container is to be disposed, ensure all product residues are removed and container is empty prior to disposal. Contact the Reusable Industrial Packaging Association (RIPA) at 301-577-3786 to find a drum reconditioner in North America (www.reusablepackaging.org).

#### 14. Transport Information:

Not considered a dangerous good according to transport regulations unless specifically cited below:

<u>Agency Proper Shipping Name</u> <u>UN Number Packing Group Hazard Class</u>

ICAO/IATA Aviation Regulated Substance, N.O.S. (Contains 3334 III 9

Hydrofluorocarbons)

#### 15. Regulatory Information:

**OSHA HAZARD COMMUNICATION STANDARD:** This material is classified as hazardous in accordance with OSHA 29 CFR 1910.1200.

SARA 311/312 Hazard Categories: Acute health hazard, chronic health hazard

#### **California Proposition 65**

#### (Safe Drinking Water and Toxic Enforcement Act of 1986)

This product contains no substances known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute unless otherwise listed:

SDS for: BAYSEAL CC XP Page 5 of 6

# Warning: This product contains chemicals known to the State of California to cause cancer and/or birth defects or other reproductive harm:

- None

# Massachusetts Right To Know List:

2-Butoxyethanol 111-76-2 1.50 %

## **New Jersey Right To Know List:**

2-Butoxyethanol 111-76-2 1.50 %

#### Pennsylvania Right To Know List:

2-Butoxyethanol 111-76-2 1.50 % Diethylene glycol 111-46-6 3.35 %

#### **SARA 302 Extremely Hazardous Substances:**

- None

# Chemicals subject to SARA 313 Reporting:

- None

# This product contains the following REACh listed Substances of Very High Concern (SVHC):

- None

 Country
 Regulation
 All Components Listed

 Canada
 Canada DSL
 Yes

 US
 Toxic Substances Control Act
 Yes

# 16. Other Information:

## Safety Data Sheet issued by Product Safety Department

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Accella Polyurethane Systems. The data on these sheets relates only to the specific material designated herein. Accella Polyurethane Systems assumes no legal responsibility for use or reliance upon this data. It is the user's responsibility to ensure that their activities comply with federal, state, or local laws.

Date revised: 2017-03-14 Reviewer Revision 0

Date Prepared: 3/20/2017

SDS for: BAYSEAL CC XP Page 6 of 6