

Breathe in luxury.

EVOLVE

PREMIUM BATH FAN

**Guaranteed performance
with revolutionary design**

**Guaranteed
performance
with**

TrueCFM™ 

Near silent



operation

**Save
up to 30%
installation
time**


**Made in
USA™**
of US & Imported Parts

Fan and fan/light models

Fan	Description
PTE511RK	50-80-110 Selectable CFM with Continuous Run Fan
PTE1115RK	110-130-150 Selectable CFM with Continuous Run Fan



Fan/Light	Description
PTEL511RK	50-80-110 Selectable CFM with Continuous Run Fan/Light
PTEL1115RK	110-130-150 Selectable CFM with Continuous Run Fan/Light



Project Pack	Description
PTE511RKF	Finish Pack: 50-80-110 Selectable CFM with Continuous Run
PTE1115RKF	Finish Pack: 110-130-150 Selectable CFM with Continuous Run
PTE511H	Housing Pack: 50-80-110 Selectable CFM
PTE1115H	Housing Pack: 110-130-150 Selectable CFM

Optional accessories

Module	Description
PES	Humidity Sensing Module
PEM	Motion Sensing Module



Model	Description
PTRD	Radiation Damper

ASHRAE 62.2-2010 Required Continuous Ventilation Rate (CFM)

Floor Area Sq. Ft.	0-1 BR	2-3 BR	4-5 BR	6-7 BR	>7 BR
<1,500	30	45	60	75	90
1,501-3,000	45	60	75	90	105
3,001-4,500	60	75	90	105	120
4,501-6,000	75	90	105	120	135
6,001-7,500	90	105	120	135	150
>7,500	105	120	135	150	165

Install EVOLVE to Guarantee Airflow

- ☒ Install the continuous run exhaust fan that guarantees airflow performance after installation.
- ☒ Have confidence in code compliance and be more efficient with fewer red tags. EVOLVE delivers the continuous ventilation rate required by codes, even when difficult installs lead to high static pressure conditions.

